EASTMAN

aviation solutions

Eastman turbo oil industry approvals

Military

| MIL SPEC | SAE | NSN | DEF STAN | NATO CODE | JSD | Package | Shelf life | Product |
|-------------------|------------|--------------------------------------|--------------------------|-----------|---------|------------|------------|------------------------------|
| MIL-PRF-23699 STD | AS5780 SPC | 9150-01-476-1074 9150-00-985-7099 | 91-101/3 | O-156 | OX-27 | 1 quart | 4 years | Eastman Turbo Oil 2380™ |
| | | None | | | | 5 gallon | 3 years | |
| | | 9150-01-476-1083 | | | | 55 gallon | 3 years | |
| MIL-PRF-7808 Gr.3 | NA | 9150-00-782-2627 | NA | O-148 | OX-9 | 1 quart | 10 years | Eastman Turbo Oil 2389™ |
| | | None | | | | 5 gallon | 3 years | |
| | | 9150-00-782-2679 | | | | 55 gallon | 3 years | |
| MIL-PRF-23699 HTS | AS5780 HPC | 9150-01-439-0756 | 91-101/3 (equivalent) | O-154 | NA | 1 quart | 10 years | Eastman - Turbo Oil 2197™ |
| | | None | | | | 5 gallon | 3 years | |
| | | 9150-01-439-2070 | | | | 55 gallon | 3 years | |
| | | None | | | | 330 gallon | 18 months | |
| | | None | | | | 350 gallon | 18 months | |
| DOD-PRF-85734 | NA | 9150-01-209-2684 | 91-100/3 | O-160 | OX-26 | 1 quart | 3 years | Eastman Turbo Oil 25™ |
| | | None | | | | 5 gallon | 3 years | |
| | | 9150-01-210-1938 | | | | 55 gallon | 3 years | |
| MIL-PRF-32538 | NA | 9150-01-682-8707 | 91-69* | O-165 | OX-125* | 55 gallon | 3 years | Eastman HALO 157™ |

This list is subject to change. Refer to your Component Maintenance Manual (CMM) or the Qualified Products List (QPL) to determine which fluids are approved for your application. If you have any questions about an application, call our customer service department at 800-260-4150.

^{*}In process



The results of insight

Eastman Corporate Headquarters P.O. Box 431 Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2020 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.